



**BAG
END**
EST. 1976

LINCOLN

LINCOLN Series

- The Lincoln series, designed by respected American engineers, is specifically tailored for the Chinese entertainment market.
- Including two-way and three-way products, Lincoln's have a clear bright upper range and deep earth shaking bass.
- The elegant design and appearance make Lincolns the ideal choice for a wide range entertainment venues.

APPLICATIONS:

KTV/ Nightclub/ Bar/ Cinema/ Auditorium/ Church/ Restaurant/ Commercial /Corporate AV

LINCOLN

TECHNICAL PARAMETERS

LINCOLN-153

Type	Three-way full-range speaker
Drivers	15" (76mm) Bass 1" (44mm) Compression tweeter 6.5" (38mm) Neodymium midrange
Frequency Response	48Hz-20KHz ± 3 dB
Power/Impedance: LF:	450W (8 Ω)
Mid-High:	200W (16 Ω)
Sensitivity (1W/1m)	102dB
Maximum Sound Pressure Level (SPL)	134dB
Dispersion:	Horizontal 90° Vertical 50°
Connector:	2 x NEUTRIK NL4
Dimensions (WxDxH)	430mmx420mmx840mm
Weight:	38kg

TECHNICAL PARAMETERS

LINCOLN-123

Type	Three-way full-range speaker
Drivers	12" (76mm) Bass 1" (38mm) Neodymium Compression tweeter 8" (65mm) Neodymium midrange
Frequency Response	50Hz-20KHz ± 3 dB
Power/Impedance: LF:	650W (8 Ω)
Sensitivity (1W/1m)	103dB
Maximum Sound Pressure Level (SPL)	135dB
Dispersion:	Horizontal 100° Vertical 100°
Connector:	1 x NEUTRIK NL4
Dimensions (WxDxH)	365mmx485mmx635mm
Weight:	33kg

LINCOLN-153



LINCOLN-123

LINCOLN

TECHNICAL PARAMETERS

LINCOLN-112

Type	Two-way rear-direction full-range speaker
Drivers	12" (76mm) Bass 1.4" (65mm) Compression tweeter
Frequency Response	50Hz-20KHz ± 3 dB
Power	700W
Impedance	8 Ω
Sensitivity (1W/1m)	99dB
Maximum Sound Pressure Level (SPL)	131dB
Dispersion:	Horizontal 80° Vertical 50°
Connector	1 x NEUTRIK NL4
Dimensions (WxDxH)	370mmx480mmx640mm
Weight	31kg

TECHNICAL PARAMETERS

LINCOLN-115

Type	Two-way full-range speaker
Drivers	15" (76mm) Bass 1.4" (65mm) Compression tweeter
Frequency Response	48Hz-20KHz ± 3 dB
Power	700W
Impedance	8 Ω
Sensitivity (1W/1m)	100dB
Maximum Sound Pressure Level (SPL)	132dB
Dispersion:	Horizontal 80° Vertical 50°
Connector	2 x NEUTRIK NL4
Dimensions (WxDxH)	430mmx425mmx690mm
Weight	34kg

LINCOLN-112



LINCOLN-115

LINCOLN

TECHNICAL PARAMETERS

LINCOLN C-112

Type	Two-way coaxial full-range speaker
Drivers	12"/(76mm) Bass 1"/(44mm) Compression tweeter
Frequency Response	50Hz-20KHz \pm 3dB
Power	500W
Impedance	8 Ω
Sensitivity (1W/1m)	99dB
Maximum Sound Pressure Level (SPL)	131dB
Dispersion:	Horizontal 80° Vertical 50°
Connector	1 x NEUTRIK NL4
Dimensions (WxDxH)	358mmx408mmx600mm
Weight	28kg

LINCOLN C-112



TECHNICAL PARAMETERS

LINCOLN-218B

Type	Horn type remote subwoofer
Drivers	2*18"/(100mm) Bass
Frequency Response	30Hz-250Hz \pm 3dB
Power	2400W
Impedance	4 Ω
Sensitivity (1W/1m)	104dB
Maximum Sound Pressure Level (SPL)	136dB
Connector	2 x NEUTRIK NL4
Dimensions (WxDxH)	1200mmx650mmx520mm
Weight	92kg

LINCOLN-218B

