

TA1202-RF TIME-ALIGN®

APPLICATIONS

Auditorium Stage Monitor House of Worship
Nightclub Installations Vocal Monitor
Electronic Keyboards

DESCRIPTION

The TA1202-RF is a compact portable full range floor monitor loudspeaker system offering both high fidelity and high efficiency. The Time-Aligned™ studio quality sound provides detail and clarity not found in other designs. Rugged Ro Tex™ finished birch plywood enclosure, recessed handle and durable grille make the TA1202-RF an ideal choice for almost all portable monitoring applications. With flat frequency response and Time-Alignment™, the TA1202-RF requires almost no equalization and delivers clear intelligible vocal reproduction with excellent gain before feedback abilities. The shallow angle design along with the rotatable 80 degree (h) by 60 degree (v) coverage pattern offers optimal mounting and coverage options when up against walls and ceilings or when used as a stage monitor.

SPECIFICATIONS

System Type:

2-way vented 0.9 ft³

Enclosure:

18 mm 13-ply birch plywood
30 degree angle floor monitor

Finish:

Black Ro Tex™ true water born environmental finish

Grille:

16 Gauge black powder coated perforated steel

Low Frequency Components:

SE-1280 12" Transducer, 2.5" Voice coil,
80 oz Magnet

High Frequency Components:

E-700 1" Exit compression driver,
1.8" Titanium diaphragm, 15 oz Magnet,
Radial waveguide

Input Connector:

Dual Neutrik® speakON

Internal Amplification:

Optional self powered

Hardware:

Recessed handle

Crossover Type:

Passive Time-Align® equalizer type at 2.5 kHz

Time Offset Between Driver:

< ± 25 Microseconds

Sensitivity:

101 dB SPL (2.83 V @ 1 m)

Frequency Response:

75 Hz to 20 kHz ±3 dB

Low Frequency Limit:

65 Hz

Maximum Calculated Continuous Acoustic Output:

127 dBSPL @ 1 m

Power Handling:

300 W continuous (IEC)
600 W program

Recommended Amplifier Power:

300 to 600 W at rated impedance

Rated Impedance:

8 ohms

Coverage Pattern:

80 degrees horizontal (-6 dB)
60 degrees vertical (-6 dB)
Rotatable horn

Recommended High Pass Filter:

60 Hz

Polarity:

A positive asymmetrical signal applied to the + terminal will result in a positive asymmetrical acoustical pressure

Dimensions:

21" h x 14" w x 11.5" d
54 cm x 36 cm x 30 cm

Weight:

39 lbs
18 kg

Custom Finishes:

Optional custom finishes include white, unfinished ready to paint and outdoor weather treatment.



TA1202-RF TIME-ALIGN®

ABOUT TIME-ALIGN® TECHNOLOGY

Time-Align® assures that the fundamental and overtones of a complex, transient, acoustical signal are presented to the listener in the same relationship as the electrical signal at the input terminals of the loudspeaker. The conventional loudspeaker spreads out the sound in time. When a rapid series of transients occur the results are blurring and lost detail. With Time-Align®, a transient is presented as a tight package of energy, with the same time relationships as the natural sound. This means that a rapid series of transients will be heard clearly.



True Time-Alignment™ requires much more than just physically lining up the loudspeaker components. It requires consideration of the driver placement, driver delay and adjustment of the crossover delay parameters. This achieves the precise simultaneous acoustical arrival time of each driver throughout the crossover region.

The first Time-Aligned™ Loudspeaker was invented by EM Long Associates in 1976 utilizing the Time-Align® generator invented and built by Ronald Wickersham. In 1980 Bag End® incorporated Time-Align® technology into our full range loudspeaker systems. Along with state-of-the-art laboratory instruments, the proprietary Time-Align® generator is still in use today to verify the time domain performance of our loudspeaker systems. When comparing a genuine Bag End® Time-Aligned™ loudspeaker system to any other, our technology and design is easy to hear and appreciate. The dramatic clarity, realism, and overall pleasant sound of our Time-Aligned™ systems are well noted worldwide.

ABOUT OUR RO TEX™ FINISH

The durable Ro Tex™ finish is found on Bag End™ "R" series or Road cabinets. Ro Tex™ is a water base, environmentally safe finish that is made in Europe and is uniquely strong and long lasting. As it solidifies and attaches to the wooden cabinet it bonds with the wood to make a super hard permanent finish. It is lightly textured offering both an attractive and rugged finish.

ABOUT BAG END® LOUSPEAKERS

Bag End loudspeakers began in 1976 in a small shop by people dedicated to the pursuit of making high quality loudspeaker systems. Over the decades Bag End® has employed the very best construction techniques and innovative acoustical designs into their products. The ground breaking introductions of the Time-Align® and ELF™ Technologies into sound reinforcement and studio monitor loudspeakers in the 1980's was followed by Minima One™ self-powered systems and the highly unique E-Trap™, electronic bass trap. Over the decades, Bag End® has been a leader in providing uniquely good sounding products and extraordinary service to our customers world wide.

DIMENSIONS

